

## Product-/datasheet

### Bambus Ekstrem LamelPlank™ 14 mm

#### Technical service

|              |                                                                  |
|--------------|------------------------------------------------------------------|
| Manufacturer | Holse & Wibroe A/S                                               |
| Vat no.      | CVR-nr. 28281439                                                 |
| Address      | Aganavej 16, 2670 Greve                                          |
| Phone        | +45 88 18 28 00                                                  |
| E-mail       | <a href="mailto:Info@holseogwibroe.dk">Info@holseogwibroe.dk</a> |
| Web-address  | <a href="http://www.holseogwibroe.dk">www.holseogwibroe.dk</a>   |

#### Specifications

|                          |                                                                     |
|--------------------------|---------------------------------------------------------------------|
| Item numbers             | 130440, 135440                                                      |
| Thickness                | 14 mm, $\pm 0,20$ mm                                                |
| Width                    | 135 mm, $\pm 0,20$ mm                                               |
| Length                   | 1830 mm, $\pm 0,50$ mm                                              |
| Density                  | Top layer approx. 1.050 kg/ CBM. Total approx. 600kg.               |
| Reaction to fire         | C <sub>fi</sub> -s1 – (EN 13501-1:2018 with clause 12.5 & 12.9)     |
| Emission of formaldehyde | E1                                                                  |
| Thermal conductivity     | 0,17 W/mK                                                           |
| Durability               | Class 1                                                             |
| Package content          | 1,98 sqm.                                                           |
| Weight/Package           | Approx 23 Kg.                                                       |
| Construction             | 3 mm Bambus Ekstrem Toplayer -installed on 11 mm multiplywood-core. |
| Mechanic                 | Click                                                               |
| Bevel                    | Micro                                                               |

#### Surface treatment

|         |                                                                                                                       |
|---------|-----------------------------------------------------------------------------------------------------------------------|
| Lacquer | Lacquered 5 times with Bona UV matt lacquer (Natural or White). Gloss 6-8.<br>Minor repairs before lacquer may occur. |
|---------|-----------------------------------------------------------------------------------------------------------------------|

## Installation & Maintenance

|                    |                                                                                                                                 |
|--------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Installation       | Installed floating.<br>Always check latest updated version at<br><a href="http://www.holseogwibroe.dk">www.holseogwibroe.dk</a> |
| Maintenance & Care | Check latest version at <a href="http://www.holseogwibroe.dk">www.holseogwibroe.dk</a>                                          |

Nov 2024