

Product-/datasheet Bambus Ekstrem™ Tongue & groove

Technical service

Manufacturer	Holse & Wibroe A/S
Vat no.	CVR-nr. 28281439
Address	Agenavej 16, 2670 Greve
Phone	+45 88 18 28 00
E-mail	Info@holseogwibroe.dk
Web-address	www.holseogwibroe.dk

Specifications

Item numbers	110404, 115404
Thickness	14 mm, ±0,20 mm
Width	142 mm, ±0,20 mm
Length	1830 mm, ±0,50 mm
Density	Approx. 1.050 kg/ Cbm
Reaction to fire	C _{fi} -s1 – (EN 13501-1:2018 with clause 12.5 & 12.9)
Emission of formaldehyde	E1
Thermal conductivity	0,24 W/mK
Durability	Class 1
Package content	1,98 sqm.
Weight/Package	Approx 29 Kg.
Construction	Solid
Mechanic	Tongue & groove 4 sides
Bevel	Micro

Surface treatment

Lacquer	Lacquered 5 times with BONA-UV matt lacquer (Natural). Gloss 6-8 Minor repairs before lacquer may occur.
Oil	Treated 3 times with WOCA hardening natural oil. Smaller cracks may occur in the surface due to the compression. Before usage, the surface should be sanded with the supplied "Net 180" and then oiled 1 time with WOCA maintenance oil.

Installation & Maintenance

Installation	To be installed fully glued or floating. Always check latest updated version at www.holseogwibroe.dk
Maintenance & Care	Check latest version at www.holseogwibroe.dk

July 2023